

KVM-6508I-19 8-port 19"LCD IP KVM SWITCH



The single-rail modular LCD KVM features an integrated 19" TFT LCD color display, one set of industrial keyboard and touchpad, and a 8-port IP KVM in 1U format. With the modular design, user only needs to take off few screws and any module can be easily detached/ re-attached again. Module replacement can be implemented with ease.

FEATURES

- * Integrated KVM module with 19" LCD monitor, keyboard/ touch pad module & a 8 port IP KVM switch within 1U chassis
 - * IP KVM functions at a remote control via IP Browser
 - * Support single rail for independent access to panel and keyboard tray
 - * Modular design for easy replacement and maintenance
 - * Comply with EIA RS-310C 19" rack mount standard
 - * Heavy-duty electroplate steel
 - * Support high resolution up to 1280 x 1024 @ 75Hz
 - * Support combo KVM module to connect servers via USB & PS/2 connection
- Installation setup can easily be done by a single person.

SPECIFICATIONS

Model number	KVM-6508I-19
LCD Display Size	19" LCD
Resolution	1280x1024@75Hz
Display Color	16.7M
Contrast	1000:1
Luminance	300cd/m ²
Viewing Angle	H: 85/85 (170°) · V: 60/80 (140°)
Pixel	0.294*0.294
Console Port	HDDB 15pin (shared with VGA,PS2 keyboard and Mouse)
PC selection	Push Buttons *8 · OSD (On Screen Display Menu) · Hot -Keys
KVM Switch	8-port
IP Browser Supported	IE6.0, Netscape7.0, Mozilla.1.6 (or above)
IP Setting	DHCP, Bootp, FixIP (DDNS supported)
IP Network Connecting Protocols	10/100 Ethernet, Telephone Line (External Modem) TCP IP ARP ICMP HTTP/HTTPS Telnet DHCP/BOOTP PPP; SMTP DNS NTP; Dynamic DNS
VGA Resolution	Max. 1280x1024 (Limited by TFT LCD monitor)
Housing	Metal
Power in	DC 12V 4A (with one AC to DC power Adapter)
Operation Temperature	0~50°C
Storage Temperature	-20 ~ 60°C
Humidity	10~80%, Non-Condensing
Size	482*526*44mm (WLH) , 19" Rack Mount / 1U
Weight	20kgs