SKL-1508/1516/1532-17 17"LCD Cat5 KVM SWITCH



Sunbox LCD Cat.5 KVM Switch integrated with 17" LCD monitor and keyboard with built-in touchpad in in an 1u housing.

The KVM switch connects up to 8/16/32 computers through cat5 cables and utilizes KVM CIM Adapter for the final linkup.

Available link distance between computer and CIM adapter is up to 40 meters (120 feet).





Features

- •Integrated KVM console with 17" LCD monitor in a single Rail housing
- ●Controls up to 8/16/32 computers by an 1u housing KVM Console
- Utilizes RJ-45 connectors and Cat 5e/6 cables to link computers
- •Supports PS/2 or USB computer types
- •Computer ports selection by OSD or hotkeys
- •Operation in 1U of rack space
- •Provides an extra console port USB & PS/2 keyboard, USB & PS/2 mouse
- •Supports external USB mouse
- Casecadable chain up to 16 additional KVM switches to control more computers
- Supports the video resolutions up to 1600x1200@60Hz within 40 meters distance
- Able to add an IP control card to upgrade into IP KVM switch

Specifications

Model no.		SKL-1508-17	SKL-1516-17	SKL-1532-17
Computer Port		8	16	32
	Resolution	1280 x1024@75Hz		
17" TFT-LCD	Display Color	16.7M		
	Contrast	1000:1		
	Luminance	300cd/m²		
	Pixel	0.264 * 0.264		
Console Port	VGA Interface	D-SUB 15pin, DDC (Display Data Channel) & DDC2B		
	Keyboard/ Mouse (Build-in)	PS/2 Keyboard, 104 keys; PS/2 Touchpad		
	Keyboard/ Mouse (External)	USB Keyboard *1 / USB Mouse *1		
Computer Interface		PS/2 or USB		
Auto-Scan Interval		5 /10 /20/ 30 sec.		
Lind Distance		40 meters (120 feet) /max.		
Selection Computes		OSD or Hot-Keys		
Power Supply		AC 100~240V input, 50~60Hz,		
Size		480*610*44mm (WLH), 19 / 1U		
Weight		20 KGS (approx.)		
Accessories		AC Power Cable and DC Adapter*1pcs, 19 Rack setup Kit* 1 set		
Options		SK-03P PS/2 Cat5 PC Module		
		SK-0	3U USB Cat5 PC N SK-100I-15: IP Card	Iodule