

RT232-2S RS-232/422/485 轉 TCP/IP 轉換器



2 個 RS-232/422/485 埠 轉 10/100 Mbps TCP/IP。

產品應用:RS-232 裝置連接上網, 門禁考勤系統網路化。

產品特性

- 2 埠 Serial 串列埠對 Ethernet 轉換器
- Serial 介面具備 1*RS232 埠及 1*R422/485 埠 (可 Auto-Detect)
- IP Search Utility：支援 Win-7/8/10, Vista, Win-XP, Win-2003 server, Win-2000
- Virtual COM 支援 Win2000、Win2003、XP、Vista、Win-7/ 8/ 10
- Digital I/O * 8 TTL
- 可選購 Din-Rail 及 Panel mounting 配件
- 具備 2 種輸入電源插座設計 (Socket 及 Terminal Block)
- Reset 系統重置出廠設定功能鍵
- 具備 Watch Dog 功能
- 軟體可透過網路線上更新
- CE / FCC & RoHS 認證

Specifications

Hardware	RT232-2S
CPU	ARM 32-bit Cortex M4 (120MHz)
SRAM	128K bytes
ROM	512K bytes Flash ROM
Ethernet	
Port Type	RJ-45 Connector
Speed	10/100Mbps (Auto-detect)
通訊 Protocol	ARP , IP , ICMP , UDP , TCP , HTTP , DHCP
連線模式	TCP Server / TCP Client / UDP / Virtual Com / Pairing
Setup	HTTP Browser Setup (IE)
Security	Login Password
Serial Port	
Port / Connector	RS-232 * 1 Port (DB-9) , RS-422 / 485 * 1 Port (Terminal Block)
Speed	300bps~230.4Kbps
Parity	None , Odd , Even , Mark , Space
Data Bit	5, 6, 7, 8
Stop Bit	1, 2
Pin Assignment	RS-232 Pins : Rx , Tx , GND , RTS , CTS , DTR , DSR , DCD RS-422 : Rx+ , Rx- , Tx+ , Tx- (Surge Protect , Over current protect) RS-485 : Data+ , Data- (Surge Protect , Over current protect)
ESD Protect	15KV ESD for all signals
Power Source	DC 9 ~24V, 300mA
LED Lamp	SYS (PWR) , DI/DO , Port 1, Port 2
Environments	Working Temp.: -10°C~70°C ; Storage Temp.: -20°C~85°C
Weight	100g
Dimension / W*D*H	90*60*20 mm